



Mod. P 105 GX

## "GALAXY GX"

### STANDARD EQUIPMENT

-Air filter -Engine starter -Fuel pump -Fuel settler -Battery -Fuel filter - Oil filter -Oil extraction pump -Radiator expansion tank -Guard Evolution control panel -Circuit breaker -Earth fault relay (manual version only) -Fuel tank -Fuel plug -Key locks -Steel structure -Hot galvanised sheet steel -Thermo-set powder paint -Sound attenuating material made from polyurethane textile according to class 1 fire resistance norms -Insulation jacket on exhaust line -Lifting eyes -Door gaskets with structural rivets (not adhesive), the same used in the automotive industry -Exhaust muffler with protection grills -Rain cap - Fuel tank retention basin.

### DETAILS

The range has always offered the best compromise between compactness and usability. Wide doors allow total access to all internal components making checks and regular maintenance very easy.



The Galaxy range includes, as standard, the well tested and reliable Guard Evolution controller, equipped with a very efficient software that has no equal in the market in terms of accuracy and number of functions.



The diesel engine exhaust tubes and the radiator's hot air expulsion are located on top of the canopy. This solution is the best compromise between effectiveness and user safety.



GALAXY GX is not only characterized by its particular frame (very high from the ground and equipped with support feet that adapt to every kind of terrain), but also by its wide air intakes for cooling.



Thanks to diligent efforts in design and testing as well as quality materials and workmanship, the Galaxy canopy is one of the most comfortable and silent in its class. No detail was overlooked in achieving an efficient electricity generator resistant to environmental agents.



All doors are properly sealed with high quality stripping gaskets, the same used in the automotive industry.



### VERSIONS

#### GV020

Length: 1860mm  
Width: 910mm  
Height: 1600mm  
Standard fuel tank : 50 Litres  
Oversized fuel tank: --Litres



#### GV030

Length: 2260mm  
Width: 1040mm  
Height: 1790mm  
Standard fuel tank: 70 Litres  
Oversized fuel tank: 160 Litres



#### GV060

Length: 2560mm  
Width: 1040mm  
Height: 1805mm  
Standard fuel tank: 70 Litres  
Oversized fuel tank: 160 Litres



#### GV100

Length: 3060mm  
Width: 1140mm  
Height: 2170mm  
Standard fuel tank: 120 Litres  
Oversized fuel tank: 360 Litres



#### GV150

Length: 4000mm  
Width: 1300mm  
Height: 2564mm  
Standard fuel tank: 120 Litres  
Oversized fuel tank: 400 Litres



#### GV200

Length: 4500mm  
Width: 1840mm  
Height: 2540mm  
Standard fuel tank: 120 Litres  
Oversized fuel tank: 900 Litres



Standard reference conditions ISO8528-1: 25°C temperature, 1-1000m altitude, 30% relative humidity, 100 kPa (1 bar) atmospheric pressure, 0.8 power factor, load balanced not distortional. The above mentioned information could be subject to change, please contact Visa S.p.A. to verify data in case of contractual obligations related to product specifications.