



## "POWERFULL B"

### STANDARD EQUIPMENT

-Air filter -Engine starter -Fuel pump -Fuel settler -Battery -Fuel filter  
 -Oil filter -Radiator expansion tank -Guard Evolution control panel -  
 Circuit breaker -Earth fault relay (manual version only) -Fuel tank  
 (capacity depending on the model) -Fuel cap -Thermo-set powder  
 paint -Exhaust muffler and flexible pipe supplied loose.



Mod. JD 250 B

### VERSIONS

T1

Standard fuel tank: 160  
Litres



T2

Standard fuel tank :520  
Litres



T3

Standard fuel tank: 890  
Litres



T4

Standard fuel tank: 1780  
Litres



### DETAILS


The range includes, as standard, the well tested and reliable Guard Evolution controller, equipped with a very efficient software that has no equal in the market in terms of accuracy and number of functions.



The POWERFULL "B" model is equipped with strong support feet to facilitate forklift handling and stabilizing the unit on uneven ground. The support feet have holes for permanently fixing the generator on site.



All "B" models are equipped with rubber anti vibration mountings, resistant to fuels and lubricants.



In all "B" models there is a metal battery rack.



All POWERFULL "B" models are provided with: 2" filler cap, fuel gauge, 1" sleeve for optional 4-level float switch.



Standard reference conditions ISO8528-1: 25°C temperature, 1-1000m altitude, 30% relative humidity, 100 kPa (1 bar) atmospheric pressure, 0.8 power factor, load balanced not distortional. The above mentioned information could be subject to change, please contact Visa S.p.A. to verify data in case of contractual obligations related to product specifications.