



Mod. D 150 M

"POWERFULL M"

STANDARD EQUIPMENT

Air filter -Engine starter -Fuel pump -Fuel settler -Battery -Fuel filter -Oil filter -Radiator expansion tank -Guard Evolution control panel -Circuit breaker -Earth fault relay (manual version only) -Fuel tank (capacity depending on the model) -Fuel plug -Thermo-set powder paint -Exhaust silencer and flexible pipe supplied loose -Open unit can be easily converted to a canopied version C - S - SS, even at a later date.

DETAILS

The range includes, as standard, the well tested and reliable Guard Evolution controller, equipped with a very efficient software that has no equal in the market in terms of accuracy and number of functions.




The POWERFULL "M" model is equipped with strong support feet to facilitate forklift handling and stabilizing the unit on uneven ground. The support feet have holes for permanently fixing the generator on site.




All POWERFULL "M" models are equipped with rubber anti vibration mountings, resistant to fuels and lubricants.



In all POWERFULL "M" models there is a metal battery rack.



All POWERFULL "M" models are provided with: 2" filler cap, fuel gauge, 1" sleeve for optional 4-level float switch.



VERSIONS

ST20

Fuel tank from 87 to 490 Litres, depending on the model



ST30

Fuel tank from 230 to 760 Litres, depending on the model



ST40

Fuel tank from 270 to 880 Litres, depending on the model



ST50

Fuel tank from 620 to 1000 Litres, depending on the model



Standard reference conditions ISO8528-1: 25°C temperature, 1-1000m altitude, 30% relative humidity, 100 kPa (1 bar) atmospheric pressure, 0.8 power factor, load balanced not distortional. The above mentioned information could be subject to change, please contact Visa S.p.A. to verify data in case of contractual obligations related to product specifications.