



Mod. JD 80 S

"POWERFULL C20S - C30S"

STANDARD EQUIPMENT

- Air filter -Engine starter -Fuel pump -Fuel settler -Battery -Fuel filter - Oil filter -Oil extracting pump -Radiator expansion tank -Guard Evolution control panel -Circuit breaker -Earth fault relay (manual version only) -Fuel tank -Fuel plug -Key lock -Steel structure -Hot galvanized sheet steel -Thermo-set powder paint -Sound attenuating material made from polyurethane textile according to class 1 fire resistance norms - Insulation jacket over exhaust line -Lifting eyes -Door gaskets with structural rivets (not adhesive) -Exhaust silencer with external protection grills -Rain cap for exhaust muffler

DETAILS

The POWERFULL C20S-C30S has always offered the best compromise between compactness and usability. Wide doors allow total access to all internal components making checks and regular maintenance very easy.



The modular structure allows the sound attenuators to be quickly disassembled giving access to engine and alternator and also reducing the space needed for transport.



The range includes, as standard, the well tested and reliable Guard Evolution controller, equipped with a very efficient software that has no equal in the market in terms of accuracy and number of functions.



Thanks to diligent efforts in design and testing as well as quality materials and workmanship, the POWERFULL canopy is one of the most comfortable and silent in its class. No detail was overlooked in achieving an efficient electricity generator resistant to environmental agents.



At the bottom and/or rear of the genset, specific air intakes have been projected to optimize the cooling flow of engine and alternator.



The POWERFULL gen set includes, as standard, the already well tested and reliable Guard Evolution controller. The great mechanical reliability of the gen set is supported by a very efficient software, that has no comparison in the market at all, in terms of accuracy and number of functions. Standard control panel equipment: large backlit display screen, emergency stop button, ignition key and circuit breaker.



VERSIONS

C20S

Length: 2800mm
Width: 1020mm
Height: 1700mm
Fuel tank from 87 to 490 Litres, depending on the model



C30S

Length: 3400mm
Width: 1020mm
Height: 2040mm
Fuel tank from 230 to 760 Litres, depending on the model



Standard reference conditions ISO8528-1: 25°C temperature, 1-1000m altitude, 30% relative humidity, 100 kPa (1 bar) atmospheric pressure, 0.8 power factor, load balanced not distortional. The above mentioned information could be subject to change, please contact Visa S.p.A. to verify data in case of contractual obligations related to product specifications.