



"POWERFULL C20SS - C50SS"

STANDARD EQUIPMENT

-Air filter -Engine starter -Fuel pump -Fuel settler -Battery -Fuel filter
 -Oil filter -Oil extracting pump -Radiator expansion tank -Guard
 Evolution control panel -Circuit breaker -Earth fault relay (manual
 version only) -Fuel tank -Fuel plug -Key locks -Steel structure -Hot
 galvanized sheet steel -Thermo-set powder paint -Sound attenuating
 material made from polyurethane textile according to class 1 fire
 resistance norms -Insulation jacket on exhaust line -Lifting eye -Door
 gaskets with structural rivets (not adhesive), the same used in the
 automotive industry -External exhaust silencer with protection grills -
 Rain cap for exhaust muffler



Mod. P 130 SS

VERSIONS

C20SS

Length: 2950mm
 Width: 1020mm
 Height: 1740mm
 Fuel tank from 87 to 490
 Litres, depending on the
 model



C30SS

Length: 3390mm
 Width: 1020mm
 Height: 1880mm
 Fuel tank from 230 to 760
 Litres, depending on the
 model



C40SS

Length: 4065mm
 Width: 1320mm
 Height: 2550mm
 Fuel tank from 270 to 880
 Litres, depending on the
 model



C50SS

Length: 5105mm
 Width: 1800mm
 Height: 2785mm
 Fuel tank from 620 to 1000
 Litres, depending on the
 model



DETAILS

The POWERFULL C20SS->C50SS range has always offered the best compromise between compactness and usability. Wide doors allow total access to all internal components making checks and regular maintenance very easy.



The modular structure allows the sound attenuators to be quickly disassembled giving access to engine and alternator and also reducing the space needed for transport.



The range includes, as standard, the well tested and reliable Guard Evolution controller, equipped with a very efficient software that has no equal in the market in terms of accuracy and number of functions.




Thanks to diligent efforts in design and testing as well as quality materials and workmanship, the POWERFULL canopy is one of the most comfortable and silent in its class. No detail was overlooked in achieving an efficient electricity generator resistant to environmental agents.



At the bottom and/or rear of the genset, specific air intakes have been projected to optimize the cooling flow of engine and alternator.



The POWERFULL genset includes, as standard, the already well tested and reliable Guard Evolution controller. The great mechanical reliability of the genset is supported by a very efficient software, that has no comparison in the market at all, in terms of accuracy and number of functions. Standard control panel equipment: large backlit display screen, emergency stop button, ignition key and circuit breaker.



Standard reference conditions ISO8528-1: 25°C temperature, 1-1000m altitude, 30% relative humidity, 100 kPa (1 bar) atmospheric pressure, 0.8 power factor, load balanced not distortional. The above mentioned information could be subject to change, please contact Visa S.p.A. to verify data in case of contractual obligations related to product specifications.

POWERFULL "SS"

gruppi elettrogeni - generating sets - stromerzeuger - groupes électrogènes - grupos electrogenos